

Technical data sheet

FV130.2

Execution for: Marine
OFFSHORE / RIVER / FERRY

Utensil washer

Programme start button: right
Working height: 845 mm
3-phase current 3 PE 460V 60Hz
Fresh water line: Soft cold water 0-3 °dH



© MEIKO 2016
Sample illustration

Technical data

Rack capacity/h (theoretical)	30 / 15 / 10 racks/h
Programme cycle time	120 / 240 / 360 s
Rack dimension	850 x 700 mm
Entry height	740 mm
Dimensions (W x H x D)	1030 x 1785 x 895 mm
Electrical feeding cable	3-phase current 3 PE 460V 60Hz nominal capacity: 14,7 kW nominal current: 20,8 A
Protection class of the machine	IP X5
Equipment	MIKE 2 control Infrared interface for wireless communication Leakage detector Soft start Wash arm drive Boiler safety device Drain pump Automatic self-cleaning when tank is drained Back wall cladding Main switch, installed Machine base in marine version
Fresh water line	Air gap 'AA' in accordance with EN 1717 with booster pump
Fresh water supply	Minimum flow pressure 60 kPa / 0,6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5,0 bar Max. supply water temperature 60 °C
Flow rate	5,0 l/min

Technical data sheet

Final rinse water quantity	5,8 liters/cycle
Boiler	Contents: 18,0 l Heater: 12,00 kW Temperature: 83 °C Tank / boiler locked
Wash tank	Filling: 85,0 l Heater: 6,00 kW Temperature: 60 °C
Wash pump	Performance: 2,20 kW
Dosing of rinse aid	Potential free terminals provided for rinse aid dosing system
Detergent dosage	Potential free terminals provided for detergent dosing system
Material	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4404
Heat emission	for 15 programme cycles/h total: 4,5 kW perceptible: 3,0 kW latent: 1,5 kW
Ventilation flow rate	1150 m ³ /h
Steam emission	2,1 kg/h
Emission sound pressure level at the workplace (LpA)	69 dB
Net weight	280,0 kg

*Note:

Electrical equipment suitable for supply voltage:
3 PE 460 V 60 HZ (3 PE 440-480 V 60 Hz)