

Technical data sheet

FV250.2

Execution for: China

Utensil washer

Programme start button: right

Working height: 845 mm

3-phase current: 3N PE 400V 50Hz

Fresh water line: Soft cold water 0-3 °dH



© MEIKO 2016
Sample illustration

Technical data

| | |
|--|---|
| Rack capacity/h (theoretical) | 30 / 15 / 7 racks/h |
| Programme cycle time | 120 / 240 / 480 s |
| Rack dimension | 1310 x 700 mm |
| Entry height | 890 mm |
| Dimensions (W x H x D) | 1490 x 1935 x 895 mm |
| Electrical feeding cable | 3-phase current 3N PE 400V 50Hz* nominal capacity: 22.9 kW nominal current: 39.4 A |
| Protection class of the machine | IP X5 |
| Equipment | MIKE 2 control Infrared interface for wireless communication Leakage detector Soft start Wash arm drive Boiler safety device Drain pump Automatic self-cleaning when tank is drained Aqua-Stop system Back wall cladding |
| Fresh water line | Air gap 'AA' in accordance with EN 1717 with booster pump |
| Fresh water supply | Minimum flow pressure 60 kPa / 0.6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5.0 bar Max. supply water temperature 60 °C |
| Flow rate | 5.0 l/min |
| Final rinse water quantity | 9.0 liters/cycle |

Technical data sheet

| | |
|---|---|
| Boiler | Contents: 18.0 l Heater: 18.00 kW Temperature: 83 °C Tank / boiler locked |
| Wash tank | Filling: 100.0 l Heater: 9.00 kW Temperature: 60 °C |
| Wash pump | Performance: 2 x 2.20 kW |
| Dosing of rinse aid | Hose pump (24 V) with time control and suction lance |
| Material | Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4404 |
| Heat emission | for 15 programme cycles/h total: 6.7 kW perceptible: 4.5 kW latent: 2.2 kW |
| Ventilation flow rate | 1710 m ³ /h |
| Steam emission | 3.2 kg/h |
| Emission sound pressure level at the workplace (LpA) | 70 dB |
| Net weight | 350.0 kg |

*Note:

Electrical equipment suitable for supply voltage:
3N PE 400 V 50 HZ (3N PE 380-415 V 50 Hz)